



Description: [Head light](#)
Part Number: 111088-111106
Application: 1999-2004 Ford F250/F350/F450



Tools needed: Phillips screwdriver, Pliers, 7mm socket, wire cutters, electrical tape.



Step 1: Remove the four Phillips screw located on top of the grill.



Step 2: Under the grill you will have to lift up the push tabs to take off the grill.



Step 3: Remove the grill.



Step 4: Unscrew the two 7mm screws located on the bottom of the parking light.



Step 5: Remove the parking light from the vehicle.



Step 6: Twist off the parking light socket.



Step 7: Twist off signal light socket.



Step 8: Use pliers to remove the two locking clips located on the top of the head light.



Step 9: Use the pliers to remove the push pin clip on the inside of the engine bay front frame.



Step 10: Take off the head light.



Step 11: Unclip the head light wire harness.



Step 12: Get the new Anzo light and splice the red (+) wire to the brown wire on the parking light.



Step 13: Splice the black (-) wire into the black wire of the parking light to light up the leds.



Step 14: Plug in the head light wire harness into the new Anzo light.



Step 15: Twist in the parking and signal light into the new Anzo head light.



Step 16: Use the supplied locking clip on the top corner to hold in the head light.



Step 17: Test all functions before driving.

