



Jeep KJ Liberty 2002-2006 2" Rear Coil Spring Spacers



Bill of Materials		
Part No.	Description	Qty
M03324	Coil Spacer R	2
M00337	Shock Boot R	2
P01055	Cable Ties	2

NOTE: SEE WARNING AT BOTTOM OF PAGE.
DO NOT COMBINE WITH ANY OTHER SUSPENSION KIT

Rear Installation Instructions

1. Raise the rear of vehicle and support with jack stands in front of the lower control arms so that the rear tires are off of the ground. Remove the rear wheels.
2. With a floor jack supporting the axle, disconnect the upper shock mounts. Figure 1.
3. Lower the axle and remove the coil springs. Figure 2.
4. Remove the lower coil spring isolator. Figure 3.
5. Install the coil spring spacer in the same position as the lower isolator. Figure 4.
6. Install the coil spring on top of the coil spring spacer. (You may have to use a coil spring compressor to reinstall the coil spring) Figure 5.
7. Raise the floor jack and reconnect the upper shock mounts and torque all bolts to factory specs.
8. Reinstall the wheels and lower the vehicle to the ground.
9. Recheck all bolts after 500 miles.
10. Upon completion of kit installation the following warning applies:

WARNING

This vehicle has been modified to enhance its performance. The steering, braking and handling of this vehicle will differ from standard passenger cars and trucks, This vehicle handles differently from an ordinary vehicle in driving conditions which may occur on streets, highways and off road.

Avoid unnecessary abrupt maneuvers, sudden stops, sharp turns and other driving conditions that could cause loss of control, possibly leading to a roll over or other accident that could result in serious injury or death to driver and passengers.

If larger tires are installed the speedometer will read lower than the vehicles actual speed.

DRIVE WITH CARE, REDUCE SPEED AND WEAR SEAT BELTS AT ALL TIMES.

This kit should be installed by a professional mechanic



Fig. 1



Fig. 2



Fig. 3



Fig. 4



Fig. 5