

INSTALLATION GUIDE

TOYOTA 4RUNNER (2014+)



Included Hardware:

- (2) 1/4" Spacers
- (2) Single Nut Retainers
- (2) Double Nut Retainers (will change)
- (2) Single Nut Retainers
- (28) 1/2" Washers (+2 in update)
- (4) M12 Metric Bolts
- (8) 1/2" Nylon Nuts
- (16) 1/2" Bolts (+2 in update)

Tools:

3/4" wrench and socket
Dremel Tool or Cutter

Skill Level:

4/5 stars (Professional install recommended)

****We Recommend installing winch prior
to bumper install****

Bumper Pieces Removal

Begin by removing plastic caps and bolts that are attached to grille and bumper as shown in photos below.



Bumper/Cover Piece Removal

Continue to unbolt and remove cover pieces as shown in photo.



Grille Removal

Remove pins and plastic caps as shown in front and behind as shown. Remove front bumper.



Bumper Pieces Removal

Next you'll need to unbolt or remove some hardware that is holding the stock bumper onto the frame.



Bumper Pieces Removal

Shown right, you'll need to remove some of the inner fender clips to gain access to some of the bolts that need to be removed to get the stock front bumper off the vehicle.



Bumper Pieces Removal

Once all of the bolts/clips are removed around the frame of bumper, you should then be able to pull on the sides near the headlight and pull away from frame.



Bumper Trimming

Trim and cut away front bumper as shown with dimensions provided. 3 1/4"



Bumper Trimming (Continued)

Continue to cut away following the body lines in photo. Shown is roughly 6" in length



Bumper Trimming (Continued)

*Additional body line dimensions shown for cutting purposes. Shown is roughly 9"




Final Bumper Trim Look

When finished cutting, it should look as shown.



Side Trim Piece

Before you place the bumper piece back on the vehicle, you will also need to trim the piece shown below. First unscrew the two bolts and one clip holding the black piece in place. Next, you'll need to trim the area shown in image. You will also need to 'shave' down the portions shown in final photo below.



Frame Mount Bracket

Attach bolt to single nut retainer as shown to the reinforcement bracket, slipping into the hole of the body frame.



Frame Mount Bracket (Continued)

Use the metric bolts and washer supplied to screw in and tighten down the frame mount bracket.



Bumper Bracket Install

Align brackets into place together as shown and hand tighten bolts and nuts. You will tighten these down later after bumper is placed and properly alligned.



Bumper Bracket Install (Continued)

Use factory bolts and new bolts supplied as shown and leave loose. Tweak the hose a little if needed to snug everything together.



Bumper Placement & Adjustment

When placing bumper onto internal frame, go at a slight downward angle and then slide up into place. Adjust to roughly 1/4" all around and tighten bolts. Add Auxillary lights at this time. Enjoy!

