



Plastic Bottle, 32 fl. oz.
078698322018

Plastic Drum, 54 gal.
078698153698

SUPER HEAVY DUTY RADIATOR CLEANER

C2232, C2249

Removes rust, scale, and deposits that can cause clogging, boil over and expensive repairs. Safe for use on plastics and all metals, including aluminum.

APPLICATIONS:

- Removes Heavy Radiator Rust Deposits in One Hour or Less

DIRECTIONS: 1. Allow engine and cooling system to cool. Use extreme caution when removing radiator cap to avoid burn injury caused by high pressure release of hot liquid or steam. See owner's manual for cap removal instructions. 2. Drain cooling system. (See DISPOSAL note, below). 3. Refill with water. 4. Start engine and flush with hose until drain water runs clear. Stop engine. 5. Close drains and add GUNK® Heavy Duty Radiator Cleaner. Fill with water and replace radiator cap. 6. Start engine and run at fast idle until engine reaches normal operating temperature. Continue for 15 minutes. 7. Repeat steps 1 and 2. Close drains. Refill with manufacturer's recommended antifreeze/water mixture. Replace radiator cap. 8. If equipped with coolant reservoir, rinse and refill with coolant mix.

STORAGE, HANDLING & DISPOSAL: Use and dispose of product, container, residue and used antifreeze/coolant and radiator fluids in accordance with all local, state and federal laws and regulations. Never pour onto ground or into storm sewer or septic systems.

DANGER: Wear safety goggles, protective gloves and avoid contamination of clothing.

FIRST AID: EYES: Flush with water for 15 minutes while lifting eyelids, and get prompt medical attention. SKIN: Wash with soap and water. If irritation persists, get prompt medical attention. INHALATION: Move to fresh air. If breathing becomes difficult, get prompt medical attention. INGESTION: DO NOT INDUCE VOMITING. Call Poison Control Center, Physician, or Hospital Emergency Room immediately.

KEEP AWAY FROM CHILDREN AND ANIMALS

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.