

## **CARB PENDING**

Recommended Air Filter Cleaning Intervals: 3000 Miles.

US Patent# US 7,263,961B2

Part # 's Secret Weapon: 304-136 US Application : 2007-2008 NISSAN 350Z 3.5L Twin Throttle Body

Parts List : 2 x Weapon\*R Intake pipe. / 2 x Weapon\*R 3" <u>Air Filter</u> / 2 x 3" coupler/ 2 x 2.5"-3" Coupler 2 x Intake Bracket kit / 8 x 3" Clamp / 2 x 15mm hose

- 1 Remove Bolts securing OEM engine cover , and remove engine cover
- 2 Remove bolts securing OEM air cleaner box, loosen clamps on OEM rubber intake pipe.
- 3 Remove the 15mm PCV hose from OEM intake.
- 4 Unplug and remove the MAF sensor unit from the OEM air intake system, put aside.
- 5 Remove the OEM rubber intake tube, remove the OEM air cleaner box by pulling upwards.
- Repeat above steps for opposite side of motor
- 6 Install the 2.5"- 3" coupler onto throttlebody, secure with OEM clamp.
- 7 Insert Weapon\*R intake pipe into the coupler, secure with clamp.
- 8 Install the OEM 15mm hose onto the Weapon\*R intake pipe and reconnect to PCV box
- 9 Insert MAF unit into end of WR intake intake tubes screw in with OEM screws
- 10 Install 3" coupler onto Secret Weapon air filter, secure with supplied clamp.
- 11 Install filter assembly onto the Weapon-R pipe , secure with OEM clamp.
- 12 Install U-shaped part of intake system bracket under the clamp on air filter.
- 13 Install the rubber mounting grommet to the closest hole to the Weapon\*R air filter.
- 14 Bend the straight portion of the intake system bracket to the Rubber mounting grommet.
- 15 Secure with washer and nut included in bracket kit.

Repeat above steps for opposite side of motor

- 16 Position air intake pipe for clearance, making sure no parts are touching any part of the vehicle.
- 17 Check for hood clearance, re-adjust intake tube for perfect fitment and clearances.
- 18 Place Weapon\*R CARB Sticker on a visible place in engine compartment. ( If Applicable )

## WARNING: EO# LABEL IS REQUIRED TO AID IN THE PASSING THE SMOG CHECK INSPECTION.

**Note:** Returned Products may be subject to a 25% restocking charge. **INSTALLED PRODUCTS ARE NON-REFUNDABLE !** Report any defective or missing parts to the authorized Weapon\*R dealer you purchased this product from. Installation does require some mechanical skills. We recommend a qualified mechanic to install this product.

