

## BFGOODRICH® MUD-TERRAIN T/A® KM2

Tire Size	Service Description	Limited Warranty	Side-wall	MSPN	Rim Width Range (inches)	Section Width on Measuring Rim Width (inches)	Overall Diameter (inches)	Tread Depth (in/32nds)	Rev/ Mile @45 mph	Max Load Single (lbs@psi)	Max Load Dual (lbs@psi)	UTQG	O.E. Fit-ments
LT215/75R15/C	100Q	Std	RWL	51738	7 - 5.5	8.5 on 6	27.9	18	746	1765@50	1610@50		
LT235/75R15/C	104Q	Std	RWL	05926	7 - 6	9.3 on 6.5	29.1	18	715	1985@50	1820@50		
LT235/70R16/C	104Q	Std	RWL	01802	7.5 - 6	9.5 on 7	29.2	18	712	1985@50	1820@50		
LT255/70R16/D	115Q	Std	RWL	10698	8 - 6.5	10.2 on 7.5	30.3	18	686	2680@65	2470@65		
LT305/70R16/D	118Q	Std	RWL	39967	9.5 - 8	12.2 on 9	33.1	20	628	2910@50	2680@50		
LT225/75R16/D	110Q	Std	RWL	30329	7 - 6	8.8 on 6	29.5	18	705	2335@65	2150@65		
LT265/75R16/E	123Q	Std	RWL	19683	8 - 7	10.5 on 7.5	31.9	18	652	3415@80	3085@80		
LT285/75R16/E	126Q	Std	RWL	12544	9 - 7.5	11.3 on 8	33.1	19	628	3750@80	3415@80		
LT315/75R16/D	121Q	Std	RWL	24970	10 - 8	12.3 on 8.5	34.8	20	598	3195@50	2910@50		
LT255/85R16/E	123Q	Std	RWL	04222	8 - 6.5	10 on 7	33.3	18	625	3415@80	3085@80		
LT305/65R17/E	121Q	Std	RWL	34424	11 - 8.5	12.2 on 9	32.8	20	634	3195@65	2910@65		
LT245/70R17/E	119Q	Std	RWL	13859	8 - 6.5	9.8 on 7	30.8	18	676	3000@80	2755@80		
LT265/70R17/E	121Q	Std	RWL	73083	8.5 - 7	10.7 on 8	31.7	18	657	3195@80	2910@80		
LT285/70R17/D	121Q	Std	RWL	37037	9 - 7.5	11.5 on 8.5	33	19	630	3195@65	2910@65		
LT305/70R17/E	121Q	Std	RWL	42197	9.5 - 8	12.2 on 9	33.9	20	614	3195@65	2910@65		
LT285/75R17/E	121Q	Std	RWL	79793	9.5 - 7.5	11.3 on 8	33.9	20	614	3195@80	2910@80		
LT255/80R17/E	121Q	Std	RWL	35737	8.5 - 6.5	10 on 7	33.3	18	625	3195@80	2910@80		
LT305/60R18/E	121Q	Std	RWL	31489	11 - 8.5	12.2 on 9	32.6	20	637	3195@65	2910@65		
LT285/70R18/E	127Q	Std	RWL	22412	9.5 - 7.5	11.5 on 8.5	33.7	20	616	3860@80	3525@80		
LT305/55R20/E	121Q	Std	RWL	20881	11 - 8.5	12.4 on 9.5	33.5	20	622	3195@65	2910@65		
LT325/60R20/D	121Q	Std	RWL	34143	12 - 9	13 on 9.5	35.6	20	584	3195@50			
30x9.50R15/C	104Q	Std	RWL	71576	8.5 - 6.5	9.5 on 7.5	29.8	18	698	1985@50			
31x10.50R15/C	109Q	Std	RWL	98952	9 - 7	10.5 on 8.5	30.8	19	675	2270@50			
33x10.50R15/C	114Q	Std	RWL	38563	9 - 7	10.5 on 8.5	32.8	18	634	2600@50			
32x11.50R15/C	113Q	Std	RWL	13833	10 - 8	11.4 on 9	31.5	20	654	2535@50			
33x12.50R15/C	108Q	Std	RWL	37047	11 - 8.5	12.5 on 10	32.8	20	634	2205@35			
35x12.50R15/C	113Q	Std	RWL	53290	11 - 8.5	12.5 on 10	34.8	20	598	2535@35			
35x12.50R17/D	119Q	Std	RWL	38371	11 - 8.5	12.5 on 10	34.8	20	598	3000@50			
37x12.50R17/D	124Q	Std	RWL	25419	11 - 8.5	12.5 on 10	36.8	20	566	3525@50			
35x12.50R18/D	118Q	Std	RWL	28459	11 - 8.5	12.5 on 10	34.8	20	598	2910@50			
37x12.50R18/D	123Q	Std	RWL	97218	11 - 8.5	12.5 on 10	36.8	20	566	3415@50			
37x12.50R20/D	120Q	Std	RWL	39143	11 - 8.5	12.5 on 10	36.8	20	566	3085@50			

Government UTQG Ratings do not apply to Light Truck tires that are LT metric or flotation size.