



DRAKE OFF ROAD JEEP TJ BILLET ANTENNA INSTALLATION INSTRUCTIONS

FITS: 1997- 2006 JEEP TJ PART NO: JP-190012-BL, JP-190012-BK

Thank you for purchasing a quality Drake Off Road product. Please refer to the installation instructions below when installing this product.

TOOLS REQUIRED:

- Allen wrench: 3mm
- 3.5mm, #28 or 9/64 in drill bit
- Phillips screwdriver
- Pliers
- Rag

INSTALLATION:

- Step 1:** Unscrew stock antenna mast by using wrench on stock antenna base flats.
- Step 2:** Remove plastic cover on stock radio antenna base by gently prying on outer edges of plastic cover.
- Step 3:** Unscrew stock mounting screws holding original base to fender.
- Step 4:** Using the three provided screws, loosely install the billet cover capturing the stock antenna base. *Note: If screws are too tight slightly open mounting holes with s 3.5mm, #28 or 9/64 in drill bit.*
- Step 5:** Insert nylon insert in top hole of billet cover.
- Step 6:** Screw antenna stud by hand into billet mast until it bottoms out.
- Step 7:** Tighten mast/stud assembly into the threaded insert, using pliers with a rag around the mast to protect finish.
DO NOT OVERTIGHTEN.
- Step 8:** Firmly tighten three mounting screws without overtightening.

SATISFACTION GUARANTEE:

If you are not happy with this product, for any reason, or found product to be defective in manufacturing, simply return it to Drake Off Road within 30 days of purchase and we will replace it - no questions asked. We stand behind our products one hundred percent, so you can sit behind the wheel with pride.

**Proof of purchase and dated receipt must be present with any return. All returned products are tested and if found to be damaged by the installer, no replacement will be issued. You pay the the cost to ship to us, we pay for the return shipping. Guarantee does not include any labor and/or tax charges incurred.*



JP-190012-BL

JP-190012-BK

