



Performance Exhaust

Instruction Manual

Power Curves Mufflers

PN# 210002 NO INSERTS

1. Lay out Mufflers and make sure you have all required tools and parts. Now remove your factory external rubber exhaust flap.
2. Measure 3-inches towards the transom and mark. It is important that the tip does not slide on any further than 3-inches, nor any less.
3. Slip turndown muffler over your factory tip with the clampless portion on the bottom side of the turndown. Do not tighten.
4. Now check for proper clearance from swim steps, steering bars, out-drives etc. before tighten down mufflers. The turndowns can be rotated from side to side to gain maximum clearance from all moving parts. (NOTE: turndown tips will work more effectively the further they are below the water line.)
5. Install the bolts into the clampless portion of the tip. It is recommended that you use anti-seize on the hardware. Using a 1/2" wrench and socket, tighten down the bolts. Tighten down the bolt closest to the muffler and then the one closest to the transom. Tighten the bolts until you can no longer rotate the tip. Next, tighten until you feel resistance or like it has bottomed out.
(Do not over tighten or force !)
6. We have supplied a copy of the California J2005 Law. We suggest keeping this in your boat at all times.

Parts List

PART #	QUANTITY	DESCRIPTION
ANTI	1	ANTI-SEZE
BO-1041	2	BOLT KIT
DE-6	1	STICKER
210002	2	POWER CURVES MUFFLERS



Limited Warranty Performance Marine Muffler

Who is covered and for how long?

Gibson Performance warrants this product to be free from defects in material and workmanship for One Year to the original purchaser on which this product was originally installed and sold within the United States.

What voids this warranty?

Failure to provide proof of purchase. Damage from collision or accidents, improper installation, altered, modified or changed in any way, or racing use.

Gibson Performance will not be responsible for:

This warranty does not cover corrosion, discoloration, internal rust, surface rust, or rust-through. Cost of labor incurred to install or remove the product. Additional parts required to complete installation, shipping charges, loss of use of boat, rentals, towing and other expenses. Damage to peeling, gaskets, burnout, cracking, cosmetic appearance and parts blown out by "back fire". Inconveniences or consequential damages occasioned by failure of the product, or expressed or implied warranty with respect to this product other than as set forth herein.

What we will do to correct the problem:

If a defect in workmanship or materials is found by our factory inspection, our sole obligation shall be to repair or replace the product. This warranty only covers the product and not the labor cost of removal, installation or shipping charges. The obligations of Gibson under this warranty are limited, and shall not exceed the cost of non-confirming parts.

Gibson Performance reserves the right to make changes in design, material and specifications as deemed necessary without prior notice. In the event that the terms are not complied with, Gibson shall be under no obligation to honor this warranty. This warranty supercedes all prior warranty statements. Effective January 1, 2005.