



## GM Cars, Trucks & Vans

262 - 400 Small Block Engines

## Melling Oil Pump Helical Asymmetrical Steel Gears Improved Efficiency, Performance, and Durability





Multi-patented design resulting in the most technically advanced performance wet sump oil pump available for GM / Chevy applications

- Reduced pressure ripple, smoother flow
- Reduced torque ripple in pump drive
- Improved distributor operation
- · Improved shaft and gear wear
- NO MORE OIL PULSING!



NEW!!
"SHARK TOOTH"
Gear Technology!!
Available in both
Billet Aluminum and Cast Iron



## (262 - 400 S.B.) OHV - 1957-04 - 8 Cyl. 10% High Volume, High Pressure Performance Oil Pump



Melling Part Number	Description
10552ST	<b>10% High Volume, High Pressure Oil Pump</b> Performance upgrade of 10553ST and 10554ST. Street and Strip Applications.



#### **Features**

- Cast iron housing & cover with phosphate coating
- Exclusive billet steel Shark Tooth helical gears reduce pressure ripple, reduce torque ripple, improve distributor operation and improve shaft and gear wear
- Includes 12550 chrome-moly steel intermediate drive shaft w/steel guide
- Drive and idler shafts extended into cover for additional support
- Cover is doweled to pump housing to ensure alignment of shaft bores
- Includes optional pressure springs (-10 psi and +10 psi) (not installed)
- Uses 3/4" diameter press fit or bolt on oil pump screen (not included)
- Includes oil pump screen gasket, assembly bolts and wrench



Melling Part Number	Description
10555ST	<b>25% High Volume, High Pressure Oil Pump</b> Performance upgrade of 10550ST. Street and Strip Applications.



#### **Features**

- · Cast iron housing & cover with phosphate coating
- Exclusive billet steel Shark Tooth helical gears reduce pressure ripple, reduce torque ripple, improve distributor operation and improve shaft and gear wear
- Includes 12550 chrome-moly steel intermediate drive shaft w/steel guide
- Drive and idler shafts extended into cover for additional support
- Cover is doweled to pump housing to ensure alignment of shaft bores
- Includes optional pressure springs (-10 psi and +10 psi) (not installed)
- Uses 3/4" diameter press fit or bolt on oil pump screen (not included)
- Includes oil pump screen gasket, assembly bolts and wrench



## (262 - 400 S.B.) OHV - 1957-04 - 8 Cyl. 25% High Volume, High Pressure Performance Oil Pump



10550ST

Description

25% High Volume, High Pressure Oil Pump Performance upgrade of M55HV. Street and Strip Applications.



#### **Features**

- Cast iron housing & cover with phosphate coating
- Exclusive billet steel Shark Tooth helical gears reduce pressure ripple, reduce torque ripple, improve distributor operation and improve shaft and gear wear
- Includes 12550 chrome-moly steel intermediate drive shaft w/steel guide
- High pressure (+10 psi) spring installed
- Includes optional standard pressure spring (not installed)
- Uses 5/8" diameter press fit oil pump screen (not included)

## (262 - 400 S.B.) OHV - 1957-04 - 8 Cyl. 25% High Volume, High Pressure Performance Oil Pump



# 10551ST Description 25% High Volume, High Pressure oil pump Performance upgrade of M155HV. Street and Strip Applications.



#### **Features**

- · Cast iron housing & cover with phosphate coating
- Exclusive billet steel Shark Tooth helical gears reduce pressure ripple, reduce torque ripple, improve distributor operation and improve shaft and gear wear
- Includes 12550 chrome-moly steel intermediate drive shaft w/steel guide
- High pressure (+10 psi) spring installed
- Includes optional standard pressure spring (not installed)
- Uses 3/4" diameter press fit oil pump screen (not included)



## (262 - 400 S.B.) OHV - 1957-04 - 8 Cyl. Standard Volume, High Pressure Performance Oil Pump



## Melling Part Number Description Standard Volume, High Pressure Oil Pump Performance upgrade of M-55. Street and Strip Applications.



#### **Features**

- Cast iron housing & cover with phosphate coating
- Exclusive billet steel Shark Tooth helical gears reduce pressure ripple, reduce torque ripple, improve distributor operation and improve shaft and gear wear
- Includes 12550 chrome-moly steel intermediate drive shaft w/steel guide
- High pressure (+10 psi) spring installed
- Includes optional yellow standard pressure spring (not installed)
- Uses 5/8" diameter press fit oil pump screen (not included)

## (262 - 400 S.B.) OHV - 1957-04 - 8 Cyl. Standard Volume, High Pressure Performance Oil Pump



Melling Part Number	Description
10554ST	<b>Standard Volume, High Pressure Oil Pump</b> Performance upgrade of M155. Street and Strip Applications.



#### **Features**

- · Cast iron housing & cover with phosphate coating
- Exclusive billet steel Shark Tooth helical gears reduce pressure ripple, reduce torque ripple, improve distributor operation and improve shaft and gear wear
- Includes 12550 chrome-moly steel intermediate drive shaft w/steel guide
- High pressure (+10 psi) spring installed
- Includes optional standard pressure spring (not installed)
- Uses 3/4" diameter press fit oil pump screen (not included)



## (262 - 400 S.B.) OHV - 1957-04 - 8 Cyl. 25% High Volume Performance Oil Pump

### **Billet Aluminum Upgrade of 10555ST**







#### **Available in 3 High Volume Options**

Melling Part Number	Description
10050ST-700CT	25% High Volume Billet Aluminum For 7" Pan. Circle Track Racing
10050ST-750SS	25% High Volume Billet Aluminum For 7-1/2" Pan. Street & Strip
10050ST-825SS	25% High Volume Billet Aluminum For 8-1/4" Pan. Street & Strip

#### **Features**

- •25% higher volume than stock oil pump
- · Lightweight billet 6061-T6 aluminum housing and cover
- Exclusive billet steel Shark Tooth helical gears reduce pressure ripple, reduce torque ripple, improve distributor operation and improve shaft and gear wear
- Includes 12550 chrome-moly steel intermediate drive shaft w/steel guide
- Supercharged inlet for improved performance at high RPM's
- Pump shafts extended into cover for additional support
- Includes optional pressure springs to increase or decrease 10 psi
- Integrated oil pickup screen







10050ST-750SS Street & Strip



10050ST-825SS Street & Strip



## (262 - 400 S.B.) OHV - 1957-04 - 8 Cyl. Standard Volume Performance Oil Pump

**Melling Part Number** 

### **Billet Aluminum Upgrade of 10552ST**

**Description** 







#### **Available in 3 Standard Volume Options**

10055ST-700CT
Standard Volume Billet Aluminum
For 7" Pan. Circle Track Racing

10055ST-750SS
Standard Volume Billet Aluminum
For 7-1/2" Pan. Street & Strip

10055ST-825SS
Standard Volume Billet Aluminum
For 8-1/4" Pan. Street & Strip

#### **Features**

- Lightweight billet 6061-T6 aluminum housing and cover
- Exclusive billet steel Shark Tooth helical gears reduce pressure ripple, reduce torque ripple, improve distributor operation and improve shaft and gear wear
- Includes 12550 chrome-moly steel intermediate drive shaft w/steel guide
- Supercharged Inlet For Improved Performance At High RPM's
- Pump shafts extended into cover for additional support
- Includes optional pressure springs to increase or decrease 10 psi
- Integrated oil pickup screen



10055ST-700CT
Circle Track Racing Only



10055\$T-750\$\$ Street & Strip



10055\$T-825\$\$ Street & Strip



#### **POWERING PERFORMANCE ENGINES FOR OVER 70 YEARS**

Melling Engine Parts are manufactured with key advantages. Each part is backed by resources, technologies and people who are the very best in the world at designing, manufacturing and building exceptional products. Melling Performance parts deliver "An Advantage by Design".