



Plastic Bottle, 12 fl. oz.
078698131627

BEARIN' SEAL® ENGINE OIL STOP LEAK

M1616

Stops leaks in rubber and elastomeric engine oil seals. Prevents oil waste and unsightly oil stains. Eliminates costly repair jobs due to leaking oil seals. Mixes with motor oils and is harmless to engine parts.

APPLICATIONS:

- Helps Stop Engine Oil Leaks Fast
- For Oil Leaks At Gaskets, Timing Chain Covers & Main Seals

DIRECTIONS: For best results, use at oil and filter change. Start engine and warm to operating temperature. Turn engine off. Add contents of container to oil and drive for 15 minutes. Leaks should stop within 48 hours or after driving for 100 miles. Continued leakage may indicate excessively worn parts, which may require mechanical replacement.

STORAGE, HANDLING & DISPOSAL: Store in a cool, dry, well ventilated area away from heat, sparks or open flames. Dispose of product, container, and residue in accordance with all local, state and federal regulations.

DANGER: Use with adequate ventilation. Avoid sparks and flames. Avoid eye and skin contact and breathing of vapors. Harmful or fatal if swallowed.

FIRST AID: EYES: Flush with running water for 15 minutes while lifting eyelids and get prompt medical attention. **SKIN:** Wash with soap and water. If irritation develops, get prompt medical attention. **INHALATION:** Move to fresh air. If breathing becomes difficult, get prompt medical attention. **INGESTION: IF SWALLOWED: DO NOT** induce vomiting. Call poison control center, physician, or hospital emergency room immediately.

KEEP AWAY FROM CHILDREN AND ANIMALS

WARNING: This product contains a chemical known to the State of California to cause cancer or birth defects or other reproductive harm.

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.