

WARNINGS / LIMITATIONS

- Mount Organizer to hitch rack before loading cargo.
- Do not use if your vehicle's exhaust pipe exits close to your hitch basket. The exhaust heat may damage your Hitch Bag Cargo Carrier and/or its contents.
- Do not exceed the manufacturer's hitch basket weight limit.



1

INSTALLATION

- Place your bag on your hitch carrier platform with the zippered openings at the top, and the side with the buckles facing out (as shown in the photo).
- Unclip the two webbing straps.
- Wrap each strap around both your Organizer and the hitch rack platform, then clip the two strap ends together.
- After loading cargo, tighten the two straps to compress your bag down tightly on to your hitch carrier rack. To release a buckle just press in the sides.

- When loading distribute the weight evenly and put heavier items on the bottom.
- For security use a small padlock on the zipper.

DRIVING

- Pack items that can be damaged by water in plastic bags.
- Do NOT exceed vehicle manufacturer's hitch rating.
- Do NOT exceed speed limit. If you hear a flapping noise when driving, immediately pull over and check to make sure all straps are secure and tight.

CARE

- To avoid mildew store your Hitch Bag Cargo Carrier only when completely dry.
- Store out of the sun in a cool, dry place.
- Polyester fabric is intended for outdoor use, but is subject to color fading. Do not store in direct sunlight for long periods.

CLEANING

- Your Roof Bag Cargo Carrier may be cleaned with a soft brush and some lukewarm water. DO NOT USE SOAP as it may remove the protective coatings added by the factory. Line dry.