



SuperBANK
ULTRACAPACITOR MODULES

Lithium
POWERCELLS
SEALED LITHIUM ION TECHNOLOGY

SuperBANK

ULTRACAPACITOR MODULES



12V-500F SuperBANKS



SB500-47

Operating Voltage: 12.0V – 16.2V, Operating Temp: -40F – 150F,
 Capacitance: 500F, Watt Hours: 18.2Wh, Max Amps: 10,000A, Max Power: 4,000W
 L: 9.48"(241mm) W: 6.93"(176mm) H: 7.48"(190mm)
 Weight: 11lbs (4.98kg)



SB500-51R available(R denotes reversed polarity)

SB500-51

Operating Voltage: 12.0V – 16.2V, Operating Temp: -40F – 150F,
 Capacitance: 500F, Watt Hours: 18.2Wh, Max Amps: 10,000A, Max Power: 4,000W
 L: 9.02"(229mm) W: 5.43"(138mm) H: 8.19"(208mm)
 Weight: 11lbs (4.98kg)



SB500-48

Operating Voltage: 12.0V – 16.2V, Operating Temp: -40F – 150F,
 Capacitance: 500F, Watt Hours: 18.2Wh, Max Amps: 10,000A, Max Power: 4,000W
 L: 10.94"(278mm) W: 6.93"(176mm) H: 7.48"(190mm)
 Weight: 11lbs (4.98kg)

12V-630F SuperBANK



SB500-27

Operating Voltage: 12.0V – 16.2V, Operating Temp: -40F – 150F,
 Capacitance: 500F, Watt Hours: 18.2Wh, Max Amps: 10,000A, Max Power: 4,000W
 L: 12.09"(198mm) W: 6.65"(166mm) H: 8.31"(170mm)
 Weight: 11lbs (4.98kg)



SB500-49

Operating Voltage: 12.0V – 16.2V, Operating Temp: -40F – 150F,
 Capacitance: 500F, Watt Hours: 18.2Wh, Max Amps: 10,000A, Max Power: 4,000W
 L: 13.90"(353mm) W: 6.93"(176mm) H: 7.48"(190mm)
 Weight: 11lbs (4.98kg)



SB630-1200

Operating Voltage: 12.0V – 14.25V, Operating Temp: -40F – 150F,
 Capacitance: 630F, Watt Hours: 16Wh, Max Amps: 15,000A, Max Power: 4,000W
 L: 7.80"(198mm) W: 6.54"(166mm) H: 6.69"(170mm)
 Weight: 8.5lbs (3.85kg)

12V-1500F SuperBANKS



SB1500-75

Operating Voltage: 12.0V – 16.2V, Operating Temp: -40F – 150F,
 Capacitance: 1500F, Watt Hours: 54.6Wh, Max Amps: 30,000A, Max Power: 12,000W
 L: 12.9"(328mm) W: 7.20"(183mm) H: 10.75"(273mm)
 Weight: 35lbs (15.87kg)



SB500-34R available (R denotes reversed polarity)

SB500-34

Operating Voltage: 12.0V – 16.2V, Operating Temp: -40F – 150F,
 Capacitance: 500F, Watt Hours: 18.2Wh, Max Amps: 10,000A, Max Power: 4,000W
 L: 10.24"(260mm) W: 6.75"(171.4mm) H: 7.20"(183mm)
 Weight: 11lbs (4.98kg)



SB500-24

Operating Voltage: 12.0V – 16.2V, Operating Temp: -40F – 150F,
 Capacitance: 500F, Watt Hours: 18.2Wh, Max Amps: 10,000A, Max Power: 4,000W
 L: 10.24"(260mm) W: 6.65"(169mm) H: 8.31"(211mm)
 Weight: 11lbs (4.98kg)



SB500-65

Operating Voltage: 12.0V – 16.2V, Operating Temp: -40F – 150F,
 Capacitance: 500F, Watt Hours: 18.2Wh, Max Amps: 10,000A, Max Power: 4,000W
 L: 11.80"(300mm) W: 7.20"(183mm) H: 6.80"(173mm)
 Weight: 11lbs (4.98kg)

12V-1000F SuperBANKS



SB1000-27

Operating Voltage: 12.0V – 16.2V, Operating Temp: -40F – 150F,
 Capacitance: 1000F, Watt Hours: 36.4Wh, Max Amps: 20,000A, Max Power: 8,000W
 L: 12.09"(198mm) W: 6.65"(166mm) H: 8.31"(170mm)
 Weight: 22lbs (9.98kg)



SB1000-31

Operating Voltage: 12.0V – 16.2V, Operating Temp: -40F – 150F,
 Capacitance: 1000F, Watt Hours: 36.4Wh, Max Amps: 20,000A, Max Power: 8,000W
 L: 12.99"(328mm) W: 6.81"(173mm) H: 8.43"(214mm)
 Weight: 22lbs (9.98kg)



SB1000-75

Operating Voltage: 12.0V – 16.2V, Operating Temp: -40F – 150F,
 Capacitance: 1000F, Watt Hours: 36.4Wh, Max Amps: 20,000A, Max Power: 8,000W
 L: 12.99"(328mm) W: 7.20"(183mm) H: 10.75"(273mm)
 Weight: 22lbs (9.98kg)

16V-430F SuperBANKS



SB430-16

Operating Voltage: 14.0V – 18.9V, Operating Temp: -40F – 150F,
 Capacitance: 430F, Watt Hours: 21.2Wh, Max Amps: 10,000A, Max Power: 4,000W
 L: 10.24"(260mm) W: 6.75"(171mm) H: 7.20"(183mm)
 Weight: 11lbs (4.98kg)

16V-1050F SuperBANKS



SB1050-31

Operating Voltage: 12.0V – 17.1V, Operating Temp: -40F – 150F,
 Capacitance: 1050F, Watt Hours: 38.2Wh, Max Amps: 31,000A, Max Power: 8,000W
 L: 12.99"(328mm) W: 6.81"(173mm) H: 8.43"(214mm)
 Weight: 22lbs (9.98kg)

LithiumPOWERCELLS

SEALED LITHIUM ION TECHNOLOGY



XS15K Ultra Safe Technology
 12V Lithium Battery, Max Amplifier Wattage: 15,00W(bursts),
 Continuous Amplifier Wattage: 7,500W, Watt Hours: 335
L: 10.24"(260mm) **W:** 6.75"(171.4mm) **H:** 7.20"(183mm)
Weight: 17lbs (7.71kg)



XS30K Ultra Safe Technology
 12V Lithium Battery, Max Amplifier Wattage: 30,00W(bursts),
 Continuous Amplifier Wattage: 15,000W, Watt Hours: 675
L: 12.99"(328mm) **W:** 6.81"(173mm) **H:** 8.43"(214mm)
Weight: 31lbs (14.1kg)



XS18KSPL
 12V Lithium Battery, Max Amplifier Wattage: 18,00W(bursts), Amp Hours: 22
 Continuous Amplifier Wattage: 9,000W, Watt Hours: 300
L: 10.24"(260mm) **W:** 6.75"(171.4mm) **H:** 7.20"(183mm)
Weight: 17lbs (7.71kg)



XS30KSPL
 12V Lithium Battery, Max Amplifier Wattage: 30,00W(bursts), Amp Hours: 40
 Continuous Amplifier Wattage: 15,000W, Watt Hours: 500
L: 12.99"(328mm) **W:** 6.81"(173mm) **H:** 8.43"(214mm)
Weight: 27lbs (12.25kg)



XS36KSPL
 12V Lithium Battery, Max Amplifier Wattage: 36,00W(bursts), Amp Hours: 44
 Continuous Amplifier Wattage: 18,000W, Watt Hours: 600
L: 12.99"(328mm) **W:** 6.81"(173mm) **H:** 8.43"(214mm)
Weight: 30lbs (13.61kg)



XS40KSPL-16V
 12V Lithium Battery, Max Amplifier Wattage: 40,00W(bursts), Amp Hours: 40
 Continuous Amplifier Wattage: 20,000W, Watt Hours: 660
L: 12.99"(328mm) **W:** 6.81"(173mm) **H:** 8.43"(214mm)
Weight: 31lbs (14.1kg)



Li1215 25A Models Also Available
 12V High Frequency Lithium Ion IntelliCHARGER
L: 8.5"(216mm) **W:** 2.6"(68mm) **H:** 3.5"(89mm)
Weight: 3.3lbs (1.5kg)



Li1625 15A Models Also Available
 16V High Frequency Lithium Ion IntelliCHARGER
L: 9.125"(232mm) **W:** 4.75"(121mm) **H:** 2.875"(73mm)
Weight: 5lbs (2.27kg)

